

Beam Balanced Pumping Unit Specification

No	UNIT TYPE	STROKE Length Max - Min	Polished Rod Capacity		Certification
1	B.25D - 53 - 30	30" - 24" - 20" - 16"	5,300	Lbs	API 11E
2	B.25D - 67 - 30	30" - 24" - 20" - 16"	6,700	Lbs	API 11E
3	B.25D - 56 - 36	36" - 30" - 24" - 20"	5,600	Lbs	API 11E
4	B.25D - 67 - 36	36" - 30" - 24" - 20"	6,700	Lbs	API 11E
5	B.40D - 89 - 36	36" - 31.5" - 28.5" - 25"	8,900	Lbs	API 11E
6	B.40D - 76 - 42	42" - 37" - 33" - 29"	7,600	Lbs	API 11E
7	B.40D - 89 - 42	42" - 37" - 33" - 29"	8,900	Lbs	API 11E
8	B.40D - 76 - 48	48" - 42" - 38" - 33.5"	7,600	Lbs	API 11E
9	B.57D - 109 - 42	42" - 33" - 31" - 25"	10,900	Lbs	API 11E
10	B.57D - 95 - 48	48" - 39" - 35.5" - 29"	9,500	Lbs	API 11E
11	B.57D - 109 - 48	48" - 39" - 35.5" - 29"	10,900	Lbs	API 11E
12	B.57D - 76 - 54	54" - 44" - 40" - 32"	7,600	Lbs	API 11E
13	B.80D - 109 - 42	42" - 34" - 31" - 25"	10,900	Lbs	API 11E
14	B.80D - 95 - 48	48" - 39" - 35.5" - 29"	9,500	Lbs	API 11E
15	B.80D - 109 - 48	48" - 39" - 35.5" - 29"	10,900	Lbs	API 11E
16	B.80D - 76 - 54	54" - 44" - 40" - 32"	7,600	Lbs	API 11E
17	B.80D - 76 - 64	64" - 51" - 47.5" - 38"	7,600	Lbs	API 11E